

PyroSlave X16 and PyroAdaptor

PyroSlave X16 is a 16-channel firework igniter specially designed for pyro technician and stage special effects professionals. In order to adapt to extreme outdoor applications, PyroSlave X16 equipped with robust aluminum housing, touch keys, metal connection terminals. PyroSlave X16 can be operated both wired and wireless. Wireless mode with dual band antennas communicate simultaneously, preventing signal interference on a single frequency band. The 2-wire PBUS technology used in wired communication can realize power supply while communicating.

SPECIFICATIONS

- \ DIMENSION: 335×165×85mm
- \ WEIGHT: 3kg
- \ OUTPUT: 16
- \ TRIGGER INDICATE: LCD display and record
- \ ADDRESS: 256 (00 to FF)
- \ CONTROL: Dual-band wireless, 2-wire PBUS (communication + charging)
- \ WIRELESS RANGE: 600m
- \ WIRED RANGE: 2000m
- \ FIRING VOLTAGE: 24V
- \ FIRING CURRENT: 5A
- \ FIRING DURATION: 500ms
- \ RESISTANCE TEST: Yes
- \ BATTERY: Support 4 * 18650 cell, 4.2V, 2500mAh per piece (battery not included)
- \ OPERATION TIME: 60h, sleep mode 2 weeks; Wired mode: non-stop
- \ CHARGING CONTROL: A PyroAdaptor support 25 units PyroSlave X16
- \ CHARGING TIME: Appr. 6h
- \ WATERPROOF LEVEL: IP65
- \ MINIMUM FIRING INTERVAL: 10ms



\ PyroSlave X16



\ PyroAdaptor

PREMIUM FACTORY - OFFICIAL DISTRIBUTOR