

SPECIFICATIONS:

COLOR FLAMER	cFlamer	cFlamer Quad	cFlamer Boom
DIMENSION (mm)	370×330×305	585×419×330	580×400×428
NET WEIGHT (kg)	20	51	54
VOLTAGE	AC 220V/110V, 50/60Hz		
POWER	400W	1500W	600W
HOUSING MATERIAL	Aluminum + 304 stainless steel		
FUEL TANK CAPACITY	5.3L	2.5L*4	5.3L
MAX. EFFECT HEIGHT	10m	10m	Sparks: 12m Flame Ball: 10m
FLUID CONSUMPTION	90ml/s	90ml/s	Fuel: 200ml/shot, HC8200: 25g/shot
MAX. FIRING DURATION	2s	2s	Not applicable
AIR TANK CAPACITY	Not applicable		8L
TANK RECHARGE TIME	Not applicable		3min
EFFECT DIRECTION	Vertical up		
PUMP	water and corrosion-resistant pump		
IGNITION	High voltage electron ignition		
IGNITOR	Dual	Quad	Dual
E-STOP CONNECTOR	YES		
ARM SAFETY INDICATOR	YES		
BUILT IN ACCUMULATOR	YES		
TILT SWITCH	YES		
FUEL	Color fluid (only support color fluid prepared from SHOWVEN additives), ISOPROPANOL, ISOPAR. HC8200 LARGE (cFlamer Boom)		
USAGE IN RAIN	YES		
SAFETY SWITCH	YES		
POWER CONNECTORS	Neutrik®powerCON TRUE1		
XLR CONNECTORS	IP65 rated 3-pin and 5-pin XLR IN/OUT		
CONTROL	DMX, 9-60V signal		
DMX CHANNELS	2 / 6	6	
WORK TEMP.	-20°C~50°C		