

SPECIFICATIONS:

COLOR FLAMER	cFlamer mVolcano	cFlamer Volcano
DIMENSION (mm)	460×330×305	690×525×375
NET WEIGHT (kg)	26	76
VOLTAGE	AC 220V/110V, 50/60Hz	
POWER	400W	2000W
HOUSING MATERIAL	Aluminum + 304 stainless steel	
FUEL TANK CAPACITY	7.5L	5L*5
MAX. EFFECT HEIGHT	10m	10m
FLUID CONSUMPTION	90ml/s	90ml/s*5
MAX. FIRING DURATION	2s	2s
EFFECT DIRECTION	5 angles	5 angles, can be together
PUMP	water and corrosion-resistant pump	
IGNITION	High voltage electron ignition	
IGNITOR	Dual	Dual*5
E-STOP CONNECTOR	YES	
ARM SAFETY INDICATOR	YES	
BUILT IN ACCUMULATOR	YES	
TILT SWITCH	YES	
FUEL	Color fluid (only support color fluid prepared from SHOWVEN additives), ISOPROPANOL, ISOPAR	
USAGE IN RAIN	YES	
SAFETY SWITCH	YES	
POWER CONNECTORS	Neutrik®powerCON TRUE1	
XLR CONNECTORS	IP65 rated 3-pin and 5-pin XLR IN/OUT	
CONTROL	DMX, 9-60V signal	
DMX CHANNELS	6	
WORK TEMP.	-20°C~50°C	