

CO₂ JET X-C1



FEATURES

- \ Compact size, Stainless steel housing
- \ 0-180° multi-output angles adjustable
- \ DNP G3/8" quick coupler

SPECIFICATIONS

- \ Dimension: 285×192×192mm
- \ Net Weight: 5kg
- \ Voltage: 110V / 220V, 50/60Hz
- \ Power: 50W
- \ Max Output Height: 8-10m



- \ Support both DMX and direct on-off control
- \ Powerful output up to 8-10m
- \ Neutrik® PowerCON TRUE1 power connector

- \ Control: DMX, Direct on-off voltage control
- \ Pressure: 60bar/870PSI
- \ Power Connectors: Neutrik® PowerCON TRUE1
- \ Interface: 3-pin XLR IN/OUT (5-pin customizable)
- \ Output angle: 0-180 degree (13 angle options)

Bubble Machine



FEATURES

- \ Compact molding structure, leak proof
- \ Higher bubble output, wider coverage
- \ Enormous bubble generation

SPECIFICATIONS

- \ Dimension: 435×266×305mm
- \ Weight: 4.8kg
- \ Voltage: AC100-240V, 50/60Hz
- \ Work Power: 30W
- \ Fluid Tray Capacity: 2L



- \ 18650 battery powered design, support 3h continuous output (depend on battery)
- \ Convenient drainage of remaining bubble fluid
- \ Control: DMX, MANUAL, WIRELESS REMOTE

- \ Bubble Fluid Consumption: 25ml/min
- \ Battery: 3pcs*18650, support 3h running time
- \ Interface: 3-pin XLR
- \ Control: DMX, manual, wireless remote
- \ Output: Up to 8m

KABUKI DROP



FEATURES

- \ Compact and exquisite design
- \ Simple structure, extremely reliable
- \ PowerCON TRUE1 TOP chassis connectors

SPECIFICATIONS

- \ Dimension: 76.5×82.5×230mm (clamps included)
- \ Weight: 1kg
- \ Input: AC110-120V/220-240V, 50/60Hz
- \ Work Power: 30W



- \ Powerful electromagnet, 20kg load capacity
- \ Quick and easy to install
- \ Simple to operate, direct on-off control

- \ Load Capacity: 20kg
- \ Control: Direct on-off voltage control
- \ Power Cable: Not included