

SPECIFICATIONS:

LOW FOG GENERATOR	CREEPER AQ mini	CREEPER AQ	CREEPER AQ PLUS
DIMENSION (mm)	460×300×324	805×390×480	950×500×540
NET WEIGHT (kg)	15	35	48
VOLTAGE	220V / 110V, 50/60Hz		
POWER	2000W	2000W	2500W
HOUSING MATERIAL	PE		
HEAT UP TIME	1-2min		
CONSUMABLE	FX-M fog fluid, Water		
OUTPUT NOZZLE	1	1	2
ATOMIZER HEADS	20	30	40
WATER TANK CAPACITY	6.5L	24L	35L
FOG FLUID TANK CAPACITY	2L	3.3L	
SUPPORT EXTERIOR WATER TANK	YES	NO	
AUTO WATER REFILLING	NO	YES	
MAX. FOG FLUID CONSUMPTION	32ml/min		
MAX.WATER CONSUMPTION	250ml/min	375ml/min	500ml/min
MAX. FOG OUTPUT	10000cuft/min	15000cuft/min	20000cuft/min
FOG OUTPUT ADJUSTMENT	1-100%		
FAN SPEED ADJUSTMENT	1-100%		
EXTERIOR WATER TANK SENSOR	NO	YES	
INTERIOR WATER TANK SENSOR	YES		
CONTINUOUS OUTPUT	YES		
MAX. COVERAGE	200 m²	300 m²	400 m²
POWER CONNECTORS	Neutrik®powerCON	Neutrik®powerCON TRUE1	
XLR CONNECTORS	NEUTRIK® 3-pin XLR IN/OUT	IP65 rated 3-pin and 5-pin XLR IN/OUT	
USAGE IN RAIN	NO	YES	
CONTROL	MANUAL, DMX, Wireless		
DMX CHANNELS	2	2 / 3	