

SPECIFICATIONS:

LOW FOG GENERATOR	CREEPER ICE	CREEPER ICE PLUS
DIMENSION (mm)	492×584×760	642×584×887
NET WEIGHT (kg)	35	45
VOLTAGE	220V / 110V, 50/60Hz	220V / 110V, 50/60Hz
POWER	220V: 3000W / 6000W 110V: 1600W / 3200W	220V: 3000W / 9000W 110V: 1600W / 4800W
HOUSING MATERIAL	PE	PE
HEAT UP TIME	30min (6000W) 50min (3200W)	40min (9000W) 70min (4800W)
CONSUMABLE	Dry ice, Water	Dry ice, Water
OUTPUT NOZZLE	1	2
DRY ICE CAPACITY	15kg	30kg
WATER TANK CAPACITY	55L	75L
WATER LEVEL INDICATOR	YES	YES
OUTPUT ADJUSTMENT	50-100%	50-100%
MAX. COVERAGE	500 m ²	800 m ²
CUMULATIVE OUTPUT TIME	5-10min	5-10min
POWER CONNECTORS	NEUTRIK®POWERCON TRUE1	5-PIN INDUSTRIAL SOCKET, POWERCON TRUE1 CUSTOMIZABLE
XLR CONNECTORS	IP65 RATED 3-PIN AND 5-PIN XLR IN/OUT	IP65 RATED 3-PIN AND 5-PIN XLR IN/OUT
USAGE IN RAIN	YES	YES
CONTROL	MANUAL, DMX, WIRELESS	MANUAL, DMX, WIRELESS
DMX CHANNELS	1	1