

SPECIFICATIONS:

PyroSlave	PyroSlave X4	PyroSlave X16	PyroSlave X32	PyroSlave C16
DIMENSION (mm)	150x165x85	335x165x85	425x165x85	295x205x91
NET WEIGHT (kg)	1.3	3	4.1	1.7
OUTPUT	4	16	32	16
TRIGGER INDICATE	OLED display and record			
ADDRESS	256 (00 to FF)	256 (00 to FF)	128	256 (00 to FF)
CONTROL	Dual-band wireless	Dual-band wireless, 2-wire PBUS (communication + charging)		
WIRELESS RANGE	600m			
WIRED RANGE	not available	2000m		
FIRING VOLTAGE	24V			12V
FIRING CURRENT	5A			
FIRING DURATION	500ms			
RESISTANCE TEST	Yes			
BATTERY	2 * 18650 cell	4 * 18650 cell (4.2V, 2500mAh), battery not included		
OPERATION TIME	60h, sleep mode 2 weeks; Wired mode: non-stop			
CHARGING TIME	4h	Appr. 6h		
CHARGING CONTROL	Type c	Max. 25 units PyroSlave per PyroAdaptor		
WIRED COMMUNICATION	not available	Max. 64 units PyroSlave per PyroAdaptor		
WATERPROOF LEVEL	IP65			N.A.
MINIMUM FIRING INTERVAL	10ms			