

## FALLING EFFECT SPARKULAR® SPECIFICATIONS:

| SPARKULAR® SERIES         |          | SPARKULAR® FALL       | SPARKULAR® miniFALL      | SPARKULAR® waverFALL                  |
|---------------------------|----------|-----------------------|--------------------------|---------------------------------------|
| MODEL                     |          | BT04 / BT05           | BT14                     | BT34/BT35                             |
| DIMENSION (mm)            |          | 196×208×192           | 150×160×240              | 309×305×285                           |
| NET WEIGHT (kg)           |          | 6                     | 3.6                      | 17                                    |
| VOLTAGE                   |          | AC 220V/110V, 50/60Hz | AC 100-240V, 50/60Hz     | AC 220V/110V, 50/60Hz                 |
| WORK POWER                |          | 500W                  | 260W                     | 500W                                  |
| HOUSING MATERIAL          |          | FR ABS                | FR ABS                   | 304 stainless steel                   |
| INTERNAL BRACKET MATERIAL |          | 304 stainless steel   |                          |                                       |
| COLOR                     |          | Black                 |                          |                                       |
| EFFECT DIRECTION          |          | Vertical Down         | Vertical Down            | -90° to 90°                           |
| HOPPER CAPACITY           |          | 280g                  | 300g                     | 400g                                  |
| EFFECT HEIGHT             | SMALL    | No data available     | No data available        | No data available                     |
|                           | MEDIUM   | 2-3m                  | 2-3m                     | No data available                     |
|                           | LARGE    | 3-4m                  | 3-4m                     | 3-4m                                  |
|                           | LARGE I  | 4-5m                  | Not Applicable           | 4-5m                                  |
|                           | LARGE II | 5-7m                  | Not Applicable           | 5-7m                                  |
| HEIGHT ADJUSTABLE BY DMX  |          | YES                   | NO                       | YES                                   |
| HC8600 CONSUMPTION RATE   |          | 20g/min               | 15g/min                  | 25g/min                               |
| SCREEN                    |          | LCD                   | LCD                      | 3.2" Color LCD screen                 |
| ARM LIGHT                 |          | NO                    | NO                       | YES                                   |
| POWER CONNECTORS          |          | POWER IN/OUT          | Neutrik®powerCON IN/OUT  | Neutrik®powerCON TRUE1 IN/OUT         |
| XLR CONNECTORS            |          | 3-pin XLR IN/OUT      | NEUTRIK®3-pin XLR IN/OUT | IP65 rated 3-pin and 5-pin XLR IN/OUT |
| USAGE IN RAIN             |          | NO                    | NO                       | YES                                   |
| CONTROL                   |          | DMX, Wireless         |                          |                                       |
| DMX CHANNELS              |          | 2                     | 2                        | 6                                     |
| WORK TEMP.                |          | -20°C~50°C            |                          |                                       |