

SPECIFICATIONS:

SPARKULAR® SERIES		SPARKULAR® JET	SPARKULAR® JET II
MODEL		BT91 / BT92	BT93 / BT94
DIMENSION (mm)		320×280×300	348×348×290
NET WEIGHT (kg)		16.5	25
VOLTAGE		AC 220V/110V, 50/60Hz	
POWER		350W	800W
HOUSING MATERIAL		304 stainless steel	Aluminum
INTERNAL BRACKET MATERIAL		304 stainless steel	
COLOR		Black	
EFFECT DIRECTION		Vertical Up, 30° and 45° angled nozzles optional	
HOPPER CAPACITY		450g	450g+450g
EFFECT HEIGHT	SMALL	4-5m	6-8m
	MEDIUM	6-8m	6-8m
	LARGE	8-10m	9-10m
HEIGHT ADJUSTABLE BY DMX		NO	NO
HC8600 CONSUMPTION RATE		6g/shot (SMALL) 15g/shot (MEDIUM / LARGE)	12-15g/shot (SMALL) 20-25g/shot (MEDIUM / LARGE)
SCREEN		LCD	3.2" Color LCD screen
ARM LIGHT		NO	YES
POWER CONNECTORS		Neutrik®powerCON TRUE1 IN/OUT	
XLR CONNECTORS		IP65 rated 3-pin and 5-pin XLR IN/OUT	
USAGE IN RAIN		YES	IPX3 certified
CONTROL		DMX	DMX, 9-60V pyro signal
DMX CHANNELS		2	
WORK TEMP.		-20°C~50°C	