

## SPECIFICATIONS:

| SPARKULAR® SERIES         |        | SPARKULAR® mini       | SPARKULAR®             | SPARKULAR® II         | SPARKULAR® MOBILE                     |
|---------------------------|--------|-----------------------|------------------------|-----------------------|---------------------------------------|
| MODEL                     |        | BT06 / BT07           | BT01 / BT02            | BT11 / BT12           | BT16                                  |
| DIMENSION (mm)            |        | 168×180×228           | 200×218×305            | 286×280×258           | 168×180×257mm                         |
| NET WEIGHT (kg)           |        | 4.5                   | 8.5                    | 9                     | 6                                     |
| VOLTAGE                   |        | AC 220V/110V, 50/60Hz |                        |                       | AC 100-240V, 50/60Hz                  |
| POWER                     |        | 380W                  | 500W                   | 500W                  | 100W                                  |
| HOUSING MATERIAL          |        | FR ABS                |                        | FR-ABS+Aluminium      |                                       |
| INTERNAL BRACKET MATERIAL |        | Stainless steel       |                        |                       |                                       |
| COLOR                     |        | Black / White         | Black                  | Black                 | Black / White                         |
| EFFECT DIRECTION          |        | Vertical Up           |                        |                       |                                       |
| HOPPER CAPACITY           |        | 100g                  | 200g                   | 300g                  | 100g                                  |
| MAX. EFFECT HEIGHT        | SMALL  | 1.5-2m                | 1.5-2.5m               | 1.5-3m                | 1.5-2m                                |
|                           | MEDIUM | 2-2.5m                | 1.5-3.5m               | 2-4.5m                | 2-3m                                  |
|                           | LARGE  | 2-3.5m                | 2-5m                   | 3-6m                  | 3-4m                                  |
| HEIGHT ADJUSTABLE BY DMX  |        | NO                    | YES                    | YES                   | NO                                    |
| HC8600 CONSUMPTION RATE   |        | 15g/min               | 20g/min                | 20g/min               | 15g/min                               |
| SCREEN                    |        | LCD                   | LCD                    | 3.2" Color LCD screen | LCD                                   |
| POWER CONNECTORS          |        | POWER IN/OUT          | POWER IN/OUT           | powerCON TRUE1 IN/OUT | powerCON TRUE1 IN/OUT                 |
| XLR CONNECTORS            |        | 3-pin                 | 3-pin                  | 3-pin and 5-pin       | 3-pin                                 |
| USAGE IN RAIN             |        | NO                    | NO                     | YES                   | NO                                    |
| CONTROL                   |        | DMX, Wireless         | DMX, Wireless optional | DMX, Wireless         | DMX, Wireless                         |
| DMX CHANNELS              |        | 2                     | 2                      | 2                     | 2                                     |
| WORK TEMP.                |        | -20°C~50°C            |                        |                       | -10°C~50°C                            |
| BUILT-IN BATTERY          |        | NO                    |                        |                       | YES                                   |
| STANDBY TIME              |        | -                     |                        |                       | HEATING OFF > 144h<br>HEATING ON > 3h |