

MULTI ANGLE SPARKULAR® SPECIFICATIONS:

SPARKULAR® SERIES		SPARKULAR® TRIPLE	SPARKULAR® SPIN	SPARKULAR® WAVER	SPARKULAR® WHEEL
MODEL		BT51 / BT52	BT81 / BT82	BT84 / BT85	BT83
DIMENSION (mm)		400×290×270	330×305×349	300×290×273	318×307×285m
NET WEIGHT (kg)		20	20	15.5	15
VOLTAGE		AC 220V/110V, 50/60Hz			AC 100-240V, 50/60Hz
WORK POWER		1500W	1000W	500W	500W
HOUSING MATERIAL		304 stainless steel			
INTERNAL BRACKET MATERIAL		304 stainless steel			
COLOR		Black	Black / White	Black	Black
EFFECT DIRECTION		one vertical nozzle+two 25° angled nozzles	two 20° angled nozzles, rotatable	-90 ~ 90° (180° waving angles)	360°
HOPPER CAPACITY		3*160g	2*200g	400g	550g
EFFECT HEIGHT	SMALL	No data available	1.5-2.5m	No data available	Up:2.8m
	MEDIUM	2-4m	2-4m	2.5-3.5m	Up:3.3m
	LARGE	2-5m	2-5m	3-4.5m	Up: 4m; Down: 7m; Rotate: 3m radius
HEIGHT ADJUSTABLE BY DMX		YES			
HC8600 CONSUMPTION RATE		3*17g/min	2*20g/min	20g/min	50g/min
SCREEN		LCD	LCD	3.2" Color LCD screen	
SCREEN		NO	NO	YES	
POWER CONNECTORS		Neutrik®powerCON TRUE1 IN/OUT			
XLR CONNECTORS		Neutrik®3-pin and 5-pin XLR IN/OUT		IP65 rated 3-pin and 5-pin XLR IN/OUT	
USAGE IN RAIN		NO	NO	NO	IPX3 certified
CONTROL		DMX	DMX, Wireless		
DMX CHANNELS		6	2 / 4	6	
WORK TEMP.		-20℃~50℃		-20℃~40℃	