

SPECIFICATIONS:

SPARKULAR® SERIES		SPARKULAR® WP	SPARKULAR® Cyclone	SPARKULAR® Cyclone II
MODEL		BT73 / BT74	BT61 / BT62	BT63 / BT64
DIMENSION (mm)		317×287×295	457×370×280	348×316×290
NET WEIGHT (kg)		14	27	16
VOLTAGE		AC 220V/110V, 50/60Hz		
POWER		700W	1700W	1500W
HOUSING MATERIAL		304 stainless steel		
INTERNAL BRACKET MATERIAL		304 stainless steel		
COLOR		Black		
EFFECT DIRECTION		Vertical Up		
HOPPER CAPACITY		1200g	500g	450g
EFFECT HEIGHT	MEDIUM	4-4.5m	Not Applicable	Not Applicable
	LARGE	5.5-6m	6-7m	Not Applicable
	LARGE I	5.5-6m	7-8m	Not Applicable
	LARGE II	Not Applicable	8-9m	Not Applicable
	LARGE III	Not Applicable	9-10m	6-10m
HC8600 CONSUMPTION RATE		25g/min	75g/min (LARGE III)	65g/min
SCREEN		3.2" Color LCD screen	LCD	3.2" Color LCD screen
ARM LIGHT		YES	NO	YES
HEIGHT ADJUSTABLE BY DMX		YES		
POWER CONNECTORS		Neutrik®powerCON TRUE1 IN/OUT		
XLR CONNECTORS		IP65 rated 3-pin and 5-pin XLR IN/OUT		
USAGE IN RAIN		IPX4	usage in rain	IPX3 certified
CONTROL		DMX		DMX, Wireless
DMX CHANNELS		2		
WORK TEMP.		-20°C~50°C		