

SONICBOOM™ X SMOKEJET SPECIFICATIONS

As a substitute of CO₂ jet, SMOKEJET becomes more and more popular in the market. Instead of cumbersome CO₂ gas tank, it uses fog fluid as fuel, which is safer, environmental friendly and with longer effects time (more than 12min after fill up). SONICBOOM not only take the advantages of SMOKEJET, but also adopting pipeline integration technology to guarantee the burst time as short as 0.2s.

Features

- No need of CO₂ tank, safer and easy carry;
- Easy installation at any angles even place upside down;
- Super long stable effects time, upto 12min after fill up;
- No generation of CO₂, environmental friendly;
- Cost effective consumables;
- SONICBOOM mode, sound and smoke double effects;
- Half power mode, lower power supply requirement;
- Unique constant pressure system, consistent smoke effect;
- Pipeline integration technology, easy maintenance, stronger burst;
- NEUTRIK® POWERCON with quality assurance;
- Multi safety status monitoring design.
- Independent smoke column color change.

Specifications

Dimension

482 x 408 x 215 mm

Weight

17.2 kg

Work Power

3000W/1500W (220V version)
2000W (110V version)

Max Output Height

10m

LED power

5W*35PCS

Heat-up Time

220V version: 5min
110V version: 7min

Max Continuous Output Duration

8s



Tank Smoke Output Capacity

55000cuft/min

Tank Smoke Output Capacity

2.5L

DMX Channels

11 and 1 channel optional

EFFECTS