

SPECIFICATIONS:

CO ₂ JET SIMULATOR	SONICBOOM® X	SONICBOOM® PLUS	SONICBOOM® II
DIMENSION (mm)	482×408×215	500×324×325	346×305×291
NET WEIGHT (kg)	17.2	28	23
VOLTAGE	220V: 3000W / 1500W 110V: 2000W	220V: 3000W / 1800W 110V: 2400W / 1800W	
HOUSING MATERIAL	Carbon steel	Stainless iron	Stainless steel
HEAT UP TIME	9-11min	9-11min	8-10min
CONSUMABLE	FX-S fog fluid	FX-S fog fluid	FX-S / FX-M fog fluid
FOG FLUID TANK CAPACITY	2.5L	5L	2L
EFFECT HEIGHT	10m	10m	10m
MAX. OUTPUT DURATION	8s	10s	8s
MAX. FOG OUTPUT	55000cuft/min	80000cuft/min	90000cuft/min
FOG FLUID CONSUMPTION	200ml/min	330ml/min	400ml/min
MACHINE INSTALLATION ANGLE	Any direction	Any direction	Any direction
LED	5W * 35pcs	9W * 38pcs	9W * 17pcs
INTERGRATED VALVE BLOCK	YES	YES	YES
SMOKE INSTANT STOP	YES	YES	YES
HIGH PRESSURE PUMP	NO	NO	YES
POWER CONNECTORS	Neutrik®powerCON	Neutrik®powerCON	Neutrik®powerCON TRUE1
XLR CONNECTORS	NEUTRIK® 3-pin and 5-pin XLR IN/OUT	NEUTRIK® 3-pin and 5-pin XLR IN/OUT	IP65 rated 3-pin or 5-pin XLR IN/OUT
CONTROL	DMX	DMX	DMX
DMX CHANNELS	1 / 11	1 / 11 / 14	1 / 11