

GAS FLAMER SPECIFICATIONS:

GAS FLAMER	uFlamer® Gasboom	uFlamer® X-Gasboom
DIMENSION (mm)	320×310×325	400×360×350
WEIGHT (kg)	13	20
INPUT AND POWER	AC 100-240V, 50/60Hz, 200W	
HOUSING MATERIAL	304 stainless steel	
EFFECT DIRECTION	Vertical	180° (±90°)
PRESET FIRING SEQUENCES	NO	83
FLAME HEIGHT	2-8m (nozzle size, firing time etc)	
NOZZLE	G16,G20,G25,GA,GB	
E-STOP INTERFACE	Yes, can be connected in series	
DUAL MAGNETIC VALVES	Yes, connect in series	
HIGH SENSITIVE FLAME MONITORING	Yes, sensitivity up to 0.1s	
INTERFACE	NEUTRIK® POWERCON TRUE1 IN/OUT, IP65 rated 3-pin and 5-pin XLR IN/OUT	
CONTROL	DMX, 9-60V pyro signal	
IGNITION	High Voltage Electron Ignition*2	
BUILT-IN BATTERY DESIGN	Yes, 4*18650 battery	Yes, 8*18650 battery
WATERPROOF	Can be used in heavy rain	
FIRING DURATION	0.1-30s	
FILTRATION	Yes	
TILT SWITCH	YES	
FUEL	LPG propane or butane gas, gas cartridges bottle, aerosol cartridges	
CARTRIDGE HOLDER	Twin cartridge holder: 2 shut-off valves and 2 non-return valves Quadruple cartridge holder: 4 shut-off valves and 4 non-return valves (optional)	
MICRO FILTER	Yes, installed between shut-off and non-return valves	