

uFlamer Max Plus



uFlamer Max Plus is a upgrade based on uFlame Max to meet professionals who want longer firing durations. It inherited all the advantages of uFlamer Max while with firing duration up to 3s.

Features

- ∨ 20m flames
- ∨ Maxi. Firing duration upto 3s
- ∨ Built-in pump and fuel tank, plug and play system
- ∨ Compact size
- ∨ Triple high voltage igniters
- ∨ Flame monitoring function
- ∨ Multi safety configurations: cascable power cut-off E-stop connector, ARM indicator light, safety switch etc.

Specifications

Dimension

690 x 475 x 415 mm

Weight

80kg

Input and Power

200-240VAC, 50/60 Hz, 2.5KW

Housing Material

304 Stainless steel

Effect Direction

Vertical

Max. Flame Height (No Wind)

Nozzle XXH: 20m

Fuels

ISOPAR G, H, L, M; ISOPROPANOL

Fuel Tank Capacity

30L

Fuel Consumption Rate

Appr. 1L/s

Interface

NEUTRIK POWERCON TRUE1 IN/OUT

Waterproof 3-pin and 5-pin XLR IN/OUT

Control

DMX, 9-60V Pyro Signal

E-stop

Yes

ARM Indicator Light

Yes

Liquid Level Sensor

Yes

Ignition

High Voltage Electron Ignition * 3

Max. Firing Duration

3s

Use in Rain

Yes

Effects