

uFlamer® Volcano



FEATURES

- \ 5-heads liquid flamer
- \ Independent control of each head
- \ Internal pump, plug and play system
- \ Flames up to 10m
- \ Reinforced stainless steel housing
- \ 25L built-in stainless steel fuel tank
- \ Compatible with automatic refueling station
- \ Real-time fuel level display
- \ Safety switch
- \ Integrated valve block design
- \ Premium and independent jet valve
- \ Customized water-proof igniter
- \ Rainproof design, can be used in rain
- \ DMX control, with both 3-pin and 5-pin XLR port
- \ Compatible with fireworks firing system

SPECIFICATIONS

- \ Dimension: 630×450×400mm
- \ Housing material: 304 stainless steel
- \ Weight: 48kg
- \ Work power: 2000W
- \ Input: 100-120V & 200-240V, 50/60hz
- \ Flame angles: 5 directions
- \ Maximum firing durations: 8s (< 4 nozzle firing together), 1.5s (5 nozzles)
- \ Fuel: isopar, isopropanol
- \ Fuel tank capacity: 25L
- \ Effect height: 8-10m (nozzle M), 6-8m (nozzle L), 4-6m (nozzle EL)
- \ Fuel consumption: 60ml/s(M), 30ml/s(L), 15ml/s(EL) per nozzle
- \ Preset firing sequence: 97
- \ Work temp.: -20°C to 50°C
- \ Interface: seetronic 3-pin & 5-pin XLR
Neutrik® powercon true1
- \ Ignition: high voltage electron ignition
- \ Control: DMX, 9-60V pyro signal
- \ Usage in rain: yes
- \ Built-in accumulator: yes
- \ Safety switch: yes
- \ Auto refueling input: yes
- \ DMX channels: 6