

SPECIFICATIONS:

PUMP STATION	uPumper P4	uPumper P20	uPumper P20H	Fueling Station
DIMENSION (mm)	580×420×460	1100×736×1095	1100×736×1095	1100×736×1095
NET WEIGHT (kg)	48	285	285	117kg
VOLTAGE	220V / 110V, 50/60Hz	AC380V		220V / 110V, 50/60Hz
WORK POWER	1800W	6KW	10KW	1800W
HOUSING MATERIAL	Stainless steel			
WORKING PRESSURE	0.8-1MPa	0.8-1.2MPa	4-5MPa	0.5-1MPa
SUPPORT FUEL	ISOPAR, ISOPROPANOL	ISOPAR L		
BUILT IN STAINLESS STEEL TANK	YES			
FLUID TANK CAPACITY	32L	250L		
PUMP OUTPUT	15L/min	110L/min		1000L/H
APPLY TO	PF10, X1800	PF10, X1800, X5	X20	Volcano, MAX, MAX PLUS
SUPPORT FLAME HEAD	4	8-20 heads, 4 heads(X5)	2-3 heads	Calculate based on pump output and firing frequency
WORKING MODE	Pressurize / Fueling	Pressurize		Fueling
DIGITAL FUEL LEVEL DISPLAY	YES			
PRESSURE MONITOR	YES			
E-STOP BUTTON	NO	YES		
E-STOP CONNECTOR	YES	NO		
ARM INDICATOR LIGHT	YES	NO		
FUEL OUTPUT COUPLER	4*ISO7241B G1/4 Female	ISO228 G1-1/4 external thread		ISO7241B G1/2 Female
FUEL INPUT QUICK COUPLER	ISO7241B G1/4 Male	NO		
POWER OUTPUT	4*Neutrik®powerCON TRUE1	NO		
POWER CONNECTORS	Neutrik®powerCON TRUE1	INDUSTRIAL POWER INPUT		Neutrik®powerCON TRUE1
XLR CONNECTORS	IP65 rated 3-pin and 5-pin XLR IN/OUT			
CONTROL	MANUAL, DMX, Wireless	DMX, AUTO		
DMX CHANNELS	6	1		
WORK TEMP.	-20°C~50°C			