

## SPECIFICATIONS:

| MACHINE                    | X-S3000                                     | P-S1500                                     | X-H2                                   | P-H3             |
|----------------------------|---------------------------------------------|---------------------------------------------|----------------------------------------|------------------|
| DIMENSION (mm)             | 660×404×290                                 | 500×315×260                                 | 845×510×850                            | 360 x 300 x 230  |
| NET WEIGHT (kg)            | 16.6                                        | 13                                          | 75                                     | 11               |
| VOLTAGE                    | 220V / 110V, 50/60Hz                        |                                             |                                        |                  |
| POWER                      | 220V: 3000W<br>110V: 2000W                  | 1500W                                       | 220V: 3000W                            | 1500W            |
| HOUSING MATERIAL           | CARBON STEEL                                |                                             | Flightcase                             | Carbon steel     |
| HEAT UP TIME               | 7min                                        | 7min                                        | 10min                                  | 4min             |
| CONSUMABLE                 | FX-M fog fluid                              |                                             | FX-HF fog fluid                        |                  |
| FOG FLUID TANK CAPACITY    | 9L                                          | 3L                                          | 4L*2                                   | 5L               |
| MAX. OUTPUT DISTANCE       | 10m                                         | 7m                                          | Not applicable                         |                  |
| MAX. FOG OUTPUT            | 40000cuft/min                               | 30000cuft/min                               | 50000cuft/min                          | 6000cuft/min     |
| OUTPUT DURATION            | 40s @100% output,<br>continuous @low output | 15s @100% output,<br>continuous @low output | Continuous<br>@output<80%              | Continuous       |
| OUTPUT ADJUSTMENT          | 1-100%                                      |                                             |                                        |                  |
| FAN SPEED ADJUSTMENT       | Not applicable                              |                                             | 1-100%                                 |                  |
| MAX. FOG FLUID CONSUMPTION | 250ml/min                                   |                                             | 350ml/min                              | 15ml/min         |
| POWER CONNECTORS           | Neutrik®powerCON                            |                                             |                                        | Power IN         |
| XLR CONNECTORS             | NEUTRIK® 3-pin and<br>5-pin XLR IN/OUT      | NEUTRIK® 3-pin XLR<br>IN/OUT                | NEUTRIK® 3-pin and<br>5-pin XLR IN/OUT | 3-pin XLR IN/OUT |
| CONTROL                    | MANUAL, DMX, Wireless                       |                                             |                                        |                  |
| DMX CHANNELS               | 1                                           |                                             | 2                                      |                  |